



EXCHANGER SIZE *BAFFLE SPACING	DIMENSIONS											
	A		B		C		D		N1		N2	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
WX-62-4*-1	29 3/4	756	16	406	7	178	26	660	2	51	2	51
WX-63-4*-1	41 3/4	1060	28	711	19	483	38	965	2	51	2	51
WX-64-4*-1	53 3/4	1365	40	1016	31	787	50	1270	2	51	2	51
WX-65-4*-1	65 3/4	1670	52	1321	43	1092	62	1575	2	51	2	51
WX-66-4*-1	77 3/4	1975	64	1626	55	1397	74	1880	2	51	2	51
WX-67-4*-1	89 3/4	2280	76	1930	67	1702	86	2184	2	51	2	51
WX-68-4*-1	101 3/4	2584	88	2235	79	2007	98	2489	2	51	2	51
WX-69-4*-1	113 3/4	2889	100	2540	91	2311	110	2794	2	51	2	51
WX-610-4*-1	125 3/4	3194	112	2845	103	2616	122	3099	2	51	2	51
WX-611-4*-1	137 3/4	3499	124	3150	115	2921	134	3404	2	51	2	51
WX-612-4*-1	149 3/4	3804	136	3454	127	3226	146	3708	2	51	2	51

NOZZLE SCHEDULE				
SERVICE	MARK	SHELL SIDE	MARK	TUBE SIDE
INLET	(N1)	AS PER TABLE	(N5)	1 1/2 (38) NPT
OUTLET	(N2)	AS PER TABLE	(N6)	1 1/2 (38) NPT
DRAIN	(N3)	1/2 (13) NPT	(N7)	1/2 (13) NPT
VENT	(N4)	3/4 (19) NPT		

NOTES: 1. SUPPORTS SUPPLIED ONLY IF SPECIFIED ON ORDER.
 2. NOZZLE SIZES SHOWN ARE RECOMMENDED FOR MAXIMUM EXCHANGER LIFE.
 3. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.
 4. DRAWING IS NOT TO SCALE.
 5. ALL DIMN'S ±1/8 (3) UNLESS OTHERWISE SHOWN.

DESIGN CONDITIONS				
	SHELL		TUBES	
DESIGN PRESSURE	150 PSIG	1034 KP ₀	150 PSIG	1034 KP ₀
DESIGN TEMPERATURE	375 °F	191 °C	375 °F	191 °C
MIN. DESIGN METAL TEMP.	35 °F	1.7 °C	35 °F	1.7 °C
HYDRO. TEST PRESSURE	225 PSIG	1551 KP ₀	300 PSIG	2068 KP ₀
CONTENTS	WATER		WATER	

CUSTOMER:
 LOCATION:
 ENGINEER:
 ORDER No.:
 PROJECT/JOB:
 LOCATION:
 TAG: (QUOTE #)

TITLE	A R M S T R O N G				NUMBER	REV.
G.A. 150 LB. WX SERIES HEAT EXCHANGERS	TORONTO - CANADA	MONTREAL - CANADA	BUFFALO - N. Y.	COLCHESTER - U.K.	WX-6-4P-1 (2)	
DATE: 12 / 01 / 94	BY: D.C.R.	TEL: (416) 755-2291	TEL: (514) 421-2424	TEL: (716) 693-8813	TEL: (44) 120-657-9491	